

100W | USB-C

X100

X100B



X100W



COMPACT AND PORTABLE. XGRID USB-C CHARGER.

2 PORT

DUAL-PORT DESIGN.

Charge any single device at 100 watts of pure power. Or charge two devices simultaneously with intelligent power sharing - 65W/30W, 45W/45W, or 30W/65W.

USB-C

FAST CHARGING.

Experience the latest fast charging technologies - Power Delivery (PD), Quick Charge (QC), and Programmable Power Supply (PPS) - to charge up all your USB-C devices faster than ever.

POWER SHARING

DYNAMIC POWER SHARING.

Seamlessly adjusts power distribution across both ports, delivering the most efficient and safe charge to each device exactly when needed.



NOCO

30339 Diamond Parkway, #102
Glenwillow, OH 44139 | USA
1.800.456.6626

no.co

CHARGE EVERYTHING.

MEET THE XGRID X100.

A sleek, 2-port charger that delivers fast charging to all devices with intelligent power sharing, ensuring a safe and reliable charging experience - your all-in-one charging solution.

CHARGE IN 4 EASY STEPS.



1. Unfold Prongs



2. Plug into Outlet



3. Plug Cord into Charger



4. Plug into Device



INTELLIGENT SAFEGUARDS.


An advanced charger that continuously monitors and adjusts, ensuring precise charging while protecting your devices from overcharging or overheating.



DYNAMIC POWER SHARING

USB-C PORT (1)	USB-C PORT (2)
100W	0W
65W	30W
45W	45W
30W	65W
0W	100W

WHAT'S IN THE BOX



*Manuals not to scale with X100



Quick Start Guide



Safety and Warranty Information

TECHNICAL SPECIFICATIONS

OPERATING INPUT VOLTAGE RANGE:	100-240VAC
AC LINE FREQUENCY:	50-60HZ
USB-C VERSION:	USB-C PD 3.0
USB-C WATTAGE:	100W
IP RATING:	IP20
OPERATING TEMPERATURE:	32° to 104°F (0° to 40°C)
STORAGE TEMPERATURE:	-4° to 176°F (-20° to 80°C)
WEIGHT:	0.58 lbs (0.26 kg)
VOLUMETRICS:	Retail Packaging: Dimensions: 4.25" x 4.21" x 1.71" Weight: 0.81 lbs UPC: 0-46221-24005-4
	Master Carton: Dimensions: 9.45" x 6.50" x 5.28" Weight: 5.53 lbs Quantity: 6 UCC: 10046221240051
	Inner Carton: Dimensions: 4.43" x 1.91" x 4.57" Weight: 0.86 lbs

NOCO

30339 Diamond Parkway, #102
Glenwillow, OH 44139 | USA
1.800.456.6626

no.co



CONFORMS TO UL STD. 62368-1
CERTIFIED TO CSA STD C22.2 No 62368-1