



COMPACT AND PORTABLE. XGRID USB-C CHARGER.

2 PORT

DUAL-PORT DESIGN.

Charge any single device at 65 watts of pure power. Or charge two devices simultaneously with intelligent power sharing - 45W/20W, 30W/30W, or 20W/45W.

USB-C

FAST CHARGING.

Experience the latest fast charging technologies - Power Delivery (PD), Quick Charge (QC), and Programmable Power Supply (PPS) - to charge up all your USB-C devices faster than ever.

POWER SHARING

DYNAMIC POWER SHARING.

Seamlessly adjusts power distribution across both ports, delivering the most efficient and safe charge to each device exactly when needed.



30339 Diamond Parkway, #102
Glenwillow, OH 44139 | USA
1.800.456.6626

no.co



CHARGE EVERYTHING.

MEET THE XGRID X65.

A sleek, 2-port charger that delivers fast charging to all devices with intelligent power sharing, ensuring a safe and reliable charging experience - your all-in-one charging solution.

CHARGE IN 4 EASY STEPS.



INTELLIGENT SAFEGUARDS.


An advanced charger that continuously monitors and adjusts, ensuring precise charging while protecting your devices from overcharging or overheating.



DYNAMIC POWER SHARING

USB-C PORT (1)	USB-C PORT (2)
65W	0W
45W	20W
20W	45W
30W	30W
0W	65W

WHAT'S IN THE BOX



*Manuals not to scale with X65



Quick Start Guide



Safety and Warranty Information

TECHNICAL SPECIFICATIONS

OPERATING INPUT VOLTAGE RANGE:	100-240VAC
AC LINE FREQUENCY:	50-60HZ
USB-C VERSION:	USB-C PD 3.0
USB-C WATTAGE:	65W
IP RATING:	IP20
OPERATING TEMPERATURE:	32° to 104°F (0° to 40°C)
STORAGE TEMPERATURE:	-4° to 176°F (-20° to 80°C)
WEIGHT:	0.31 lbs (0.14 kg)
VOLUMETRICS:	Retail Packaging: Dimensions: 3.72" x 3.68" x 1.63" Weight: 0.50 lbs UPC: 0-46221-24003-0
	Master Carton: Dimensions: 8.27" x 6.50" x 4.65" Weight: 3.55 lbs Quantity: 6 UCC: 10046221240037
Inner Carton: Dimensions: 3.84" x 1.91" x 3.98" Weight: 0.54 lbs	

NOCO

30339 Diamond Parkway, #102
Glenwillow, OH 44139 | USA
1.800.456.6626

no.co



CONFORMS TO UL STD. 62368-1
CERTIFIED TO CSA STD C22.2 No 62368-1